

WHAT IS CLAIMED IS:

SUB  
A1

5

1. An aqueous ink comprising a colored resin dispersed therein, the colored resin comprising a film-forming resin and a colorant dispersed in a monomolecular state in the film-forming resin.

10

2. The aqueous ink according to claim 1, wherein the film-forming resin has a minimum film-forming temperature (MFT) of not higher than 35°C.

15

3. The aqueous ink according to claim 2, wherein said minimum film-forming temperature is not higher than 25°C.

20

4. The aqueous ink according to claim 3, wherein said minimum film-forming temperature is not higher than 10°C.

25

5. The aqueous ink according to claim 1, wherein the colorant is a slightly water-soluble dye or a pigment, and is contained in the film-forming resin in a monomolecular state by aid of a solubilizer.

25

6. The aqueous ink according to claim 1 which is used for ink-jet recording.

SUB  
A2

7. An ink-jet recording method comprising a

step of ejecting the aqueous ink according to claim 6 through an orifice in correspondence with a recording signal to deposit the ejected ink onto a recording medium.

5

8. An ink-jet recording apparatus comprising an ink container containing the aqueous ink according to claim 6, and a head for ejecting the ink through an orifice in correspondence with a recording signal.

10

9. An ink cartridge comprising an ink container containing the aqueous ink according to any of claims 1 to 6.

SUB  
A2

15

10. A recording unit comprising an ink container containing the aqueous ink according to claim 6, and a head for ejecting the ink through an orifice in correspondence with a recording signal.

20

11. A coloring material comprising colored resin particles which comprise a film-forming resin, and a colorant dispersed in a monomolecular state in the film-forming resin.

25

12. The coloring material according to claim 11, wherein the film-forming resin has a minimum film-forming temperature (MFT) of not higher than 35°C.

14. The coloring material according to claim 13,  
wherein said minimum film-forming temperature is not  
higher than 10°C.

15. The coloring material according to claim 11,  
10 which is used in an ink for ink-jet recording.